



MEIKO

UPster K Rack Conveyor

Rack conveyor dishwashers

Passing height 508 mm

508

mm passing height

160

L/h rinse water

WHERE TO USE



Hotel



Restaurant



Hospital



Commercial kitchen

KEY BENEFITS

- ✓ Passing height 508 mm
- ☀ Modular design fits any kitchen layout
- ⚡ 3/N/PE 400 V 50 Hz; main switch by customer

SPECIFICATIONS

Passing height	508 mm
Rinse water (continuous)	160 L/h

MODELS AT A GLANCE

Model / code	Rack capacity (prog. 1-2-3)	Total connected load, kW incl. heat recovery & drying	Power consumption, kW average, per MEIKO	Machine length, mm excl. / incl. drying	Notes
UPster K-S 160	80 - 120 - 160 racks/h	24.7	16.6	1,300 / 1,900	Less water & energy than previous model (per MEIKO)
UPster K-S 200	95 - 150 - 200 racks/h	25.2	17.0	1,550 / 2,150	
UPster K-M 250	125 - 190 - 250 racks/h	25.2	17.0	2,050 / 2,650	Pre-wash zone
UPster K-M 280	140 - 210 - 280 racks/h	26.9	18.1	2,350 / 2,950	
UPster K-L 340	170 - 260 - 340 racks/h	33.4	22.5	2,850 / 3,450	

Call SKS Sirius for prices
Ask us about this product today

TEL
1 700 81 6627

WHATSAPP
016-715 6826